



# LED DOWNLIGHTS

 **OHYAMA LIGHTS**®

DIVISION OF IRIS USA, Inc.

# OLEDL Series



- Quick Installation
- Diffused, Non-Glare Lens
- CRI: >80
- Beam Angle: 112°
- Warranty: 5 Years
- L70: >100,000 Hours
- Input Rating –AC: 100~277V; 50/60 Hz
- Dimming: 0-10V
- Max. Operation Temp: 50°C
- Min. Operation Temp: -10°C
- IP54 Rated
- Acrylic Lens
- Aluminum Frame

## 6 Inch

- Round: 7.0" x 2.91"  
(178 mm x 74 mm)  
2.43 lbs (1.1 kg)

## 8 Inch

- Round: 9.29" x 2.91"  
(236 mm x 74 mm)  
5.03 lbs (2.28 kg)
- Square: 8.81" x 8.81" x 2.91"  
(224 mm x 224 mm x 74 mm)  
5.03 lbs (2.28 kg)

## 12 Inch

- Round: 11.69" x 2.91"  
(297 mm x 74 mm)  
7.72 lbs (3.5 kg)
- Square: 11.81" x 11.81" x 2.91"  
(300 mm x 300 mm x 74 mm)  
7.72 lbs (3.5 kg)

The Ohyama Lights' LED downlights will revolutionize commercial ceilings. These slim, low-profile fixtures are designed to present a smooth, continuous look in drywall and grid ceilings. Available in round and square, downlights present an even, indirect illumination that is also dimmable. Downlights have a solid aluminum frame and industrial clips to hold the fixture in place and allow for easy installation.

ITEM	MODEL	SIZE/SHAPE	CCT	LUMENS	WATTS	Lm/W
399573	OLEDL6-13WR-UNV	6" Round	3000K	1100	13	84
399574	OLEDL6-13NR-UNV	6" Round	4000K	1200	13	92
399575	OLEDL8-13NS-UNV	8" Square	4000K	1200	13	92
399576	OLEDL8-13NR-UNV	8" Round	4000K	1200	13	92
399577	OLEDL12-16NS-UNV	12" Square	4000K	1500	16	94
399578	OLEDL12-16CS-UNV	12" Square	5000K	1500	16	94
399558	OLEDL12-16WR-UNV	12" Round	3000K	1370	16	85
399579	OLEDL12-16NR-UNV	12" Round	4000K	1500	16	94
399580	OLEDL12-16CR-UNV	12" Round	5000K	1500	16	94

