



LED FLOOD LIGHT

 **OHYAMA LIGHTS**[®]
DIVISION OF IRIS USA, Inc.

OLFL SERIES



- CCT: 3000K/ 5000K
- CRI: ≥80
- Beam Angle: 30°/60°/80°
- Warranty: 5 Years
- L70: ≥100,000 Hours
- Input Rating-AC: 120~277V/ 60Hz
- Max. Operation Temp: 50°C
- Min. Operation Temp: -20°C
- IP65 Rated
- Color Options:
Black, White, or Bronze

68 Watt /40 Watt

- W: 10.0"/9.25"
- H: 9.96"/ 8.58"
- D: 2.72"/ 2.72"
- Weight: 5.07 lbs/ 3.97 lbs

The Ohyama Lights LED Flood Lights are designed to reduce operation and energy costs to illuminate buildings, signage and flags. The 68 watt flood replaces a 175 watt HID fixture, while the 40 watt flood replaces a 100 watt HID fixture. Durable construction and engineered for long-life, the flood lights have adjustable brackets and three beam angles (30°, 60°, and 80°) for flexible installations. The Ohyama Lights LED Flood Light is made of powder coated cast aluminum with a polycarbonate lens (IP65) and is UL and DLC listed.

SERIES		WATT	CCT		BEAM ANGLE	COLOR
OLFL	-	4-40W	W-3000K	-	30	WH - white
		7-68W	C-5000K		60	BK - black
					90	BR - bronze

Example: OLFL-7W-30BR

